

# ULTRA LOW NO<sub>x</sub> FLARE

## FEATURES & BENEFITS

- Emission Limits: 0.025 NO<sub>x</sub> and 0.06 CO
- Greater than 99.5% Destruction Efficiency
- Compact Design/Small Footprint
- Proprietary Burner Technology
- 100% Stainless Steel Burner
- Long Burner Life
- Meets SCAQMD Emission Standards
- Automatic Air Fuel Ratio Control



Phone: (417) 256-2002  
sales@perennialenergy.com

# ULTRA LOW NO<sub>x</sub> FLARE

## STANDARD EQUIPMENT

- Combustion Air Blower w/ Inlet Air Filter
- High Temperature Louvers
- U.L. Listed Control Panel
- 4" Ceramic Fiber Blanket Insulation (250°F Skin Temperature)
- Stainless Steel Weather & Heat Protection At Top of Flare
- High Temperature Paint System
- O.S.H.A. Compliant Ladder System



## OPTIONAL EQUIPMENT

- Platform
- Heat Shield
- Remote Monitoring
- Gas Handling System
- Micro Flare
- Other Fuels & Waste Gases
- Custom Ratings
- Foundation Template for Easy Installation



Phone: (417) 256-2002  
sales@perennialenergy.com

**PERENNIAL  
ENERGY**  
www.PerennialEnergy.com